

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Air (psi)	Max Load (lbs)		Rim	
								S	D	Measuring	Approved
14699		185/65R14		86	H	4	44	1,168	-	5.5	5.0~6.5
14163		185/60R15		84	H	4	44	1,102	-	5.5	5.0~6.5
15120		195/60R15		88	H	4	44	1,235	-	6.0	5.5~7.0
14979		185/65R15		88	H	4	44	1,235	-	5.5	5.0~6.5
15711		195/65R15		91	H	4	44	1,356	-	6.0	5.5~7.0
14386		195/65R15		91	T	4	44	1,356	-	6.0	5.5~7.0
13466		195/65R15		91	T	4	44	1,356	-	6.0	5.5~7.0
15117		205/65R15		94	H	4	44	1,477	-	6.0	5.5~7.5
15521		185/55R16		83	H	4	51	1,074	-	6.0	5.0~6.5
16407		185/60R16		86	H	4	51	1,168	-	5.5	5.0~6.5
15517		195/50R16		84	V	4	51	1,102	-	6.0	5.5~7.0
15523		195/55R16		87	V	4	51	1,201	-	6.0	5.5~7.0
15518		205/50R16		87	V	4	51	1,201	-	6.5	5.5~7.5
14194		205/55R16		91	H	4	44	1,356	-	6.5	5.5~7.5
15710		205/55R16		91	V	4	44	1,356	-	6.5	5.5~7.5
15605		205/60R16		92	H	4	44	1,389	-	6.0	5.5~7.5
13904		205/65R16		95	H	4	44	1,521	-	6.0	5.5~7.5
15677	P	205/70R16		96	H	4	44	1,565	-	6.0	5.0~7.0
14369		215/55R16	XL	97	H	4	50	1,609	-	7.0	6.0~7.5
14691		215/60R16		95	V	4	44	1,521	-	6.5	6.0~7.5
14693		215/65R16		98	V	4	44	1,653	-	6.5	6.0~7.5
15352		225/50R16		92	H	4	51	1,389	-	7.0	6.0~8.0
14705		225/55R16		95	V	4	51	1,521	-	7.0	6.0~8.0
14702		225/60R16		98	V	4	44	1,653	-	6.5	6.0~8.0
15118		225/65R16		100	H	4	44	1,764	-	6.5	6.0~8.0
15123		235/60R16		100	H	4	44	1,764	-	7.0	6.5~8.5
15119		235/65R16		103	H	4	44	1,929	-	7.0	6.5~8.5
15347		205/45R17		84	H	4	51	1,102	-	7.0	6.5~7.5
14749		215/45R17		87	H	4	44	1,201	-	7.0	7.0~8.0
15712		205/50R17	XL	93	V	4	50	1,433	-	6.5	5.5~7.5
15530		205/55R17		91	H	4	51	1,356	-	6.5	5.5~7.5
16094		205/55R17		91	H	4	51	1,356	-	6.5	5.5~7.5
14697		215/50R17		91	V	4	51	1,356	-	7.0	6.0~7.5
15606		215/55R17		94	V	4	44	1,477	-	7.0	6.0~7.5
16383		215/55R17		94	V	4	44	1,477	-	7.0	6.0~7.5
14698		215/60R17		96	V	4	44	1,565	-	6.5	6.0~7.5
14198		225/45R17		91	W	4	44	1,356	-	7.5	7.0~8.5
14701		225/50R17		94	V	4	51	1,477	-	7.0	6.0~8.0
14694		225/55R17		97	V	4	51	1,609	-	7.0	6.0~8.0
15121		225/60R17		99	H	4	44	1,709	-	6.5	6.0~8.0
14753		235/45R17		94	V	4	51	1,477	-	8.0	7.5~9.0
15353		235/50R17		96	H	4	51	1,565	-	7.5	6.5~8.5
14704		235/55R17		99	V	4	51	1,709	-	7.5	6.5~8.5
14712		245/45R17		95	V	4	51	1,521	-	8.0	7.5~9.0
15520	P	245/50R17		98	V	4	51	1,653	-	7.5	7.0~8.5
13962		215/45R18		89	V	4	44	1,279	-	7.0	7.0~8.0
15359		215/55R18		95	H	4	51	1,521	-	7.0	6.0~7.5

14708		225/40R18	88	W	4	51	1,235	-	8.0	7.5~9.0
15348		225/45R18	91	H	4	51	1,356	-	7.5	7.0~8.5
14706		225/50R18	95	V	4	51	1,521	-	7.0	6.0~8.0
14710		225/55R18	98	V	4	51	1,653	-	7.0	6.0~8.0
15122		225/60R18	100	H	4	44	1,764	-	6.5	6.0~8.0
15346		235/40R18	91	H	4	51	1,356	-	8.5	8.0~9.5
15349		235/45R18	94	H	4	51	1,477	-	8.0	7.5~9.0
15356		235/50R18	97	H	4	51	1,609	-	7.5	6.5~8.5
15524		235/55R18	100	H	4	51	1,764	-	7.5	6.5~8.5
14714		245/40R18	93	V	4	51	1,433	-	8.5	8.0~9.5
15351		245/45R18	96	H	4	51	1,565	-	8.0	7.5~9.0
15357		245/50R18	100	H	4	51	1,764	-	7.5	7.0~8.5
15525	P	245/55R18	102	H	4	51	1,874	-	7.5	7.0~8.5
15360		225/55R19	99	H	4	51	1,709	-	7.0	6.0~8.0

. Technical Data can be changed without further notice.

. For more detail OE application information, please refer to "Original Equipment 2020" page.

Section	Overall Width (inch)	Tread Diameter (inch)	Tread Depth (/32")	U.T.Q.G			MSRP	OE
				Treadwear	Traction	Temp.		
7.4	23.5	9.0	600	A	A	Black	66.98	
7.6	23.7	9.0	440	A	A	Black	75.98	
7.9	24.2	9.0	600	A	A	Black	76.98	
7.4	24.4	9.0	500	A	A	Black	71.98	
7.9	25.0	9.0	600	A	A	Black	76.98	
7.9	25.0	9.0	500	A	A	Black	76.98	HYUNDAI
7.9	25.0	9.0	500	A	A	Black	76.98	KIA
8.2	25.5	9.0	600	A	A	Black	80.98	
7.6	24.0	9.0	600	A	A	Black	80.98	
7.4	24.7	9.0	600	A	A	Black	104.98	
7.9	23.7	9.0	600	A	A	Black	86.98	
7.9	24.4	9.0	600	A	A	Black	89.98	
8.4	24.1	9.0	600	A	A	Black	91.98	
8.4	24.9	10.0	560	A	A	Black	93.98	HYUNDAI
8.4	24.9	10.0	600	A	A	Black	93.98	
8.2	25.7	9.0	500	A	A	Black	91.98	HYUNDAI, KIA
8.2	26.5	10.0	440	A	A	Black	96.98	KIA
8.2	27.3	9.0	600	A	A	Black	96.98	
8.9	25.3	10.0	440	A	A	Black	95.98	RAM
8.7	26.1	9.0	600	A	A	Black	92.98	
8.7	27.0	9.0	600	A	A	Black	95.98	
9.2	24.9	9.0	600	A	A	Black	98.98	
9.2	25.7	9.0	600	A	A	Black	100.98	
9.0	26.6	9.0	600	A	A	Black	96.98	
9.0	27.5	9.0	600	A	A	Black	103.98	
9.4	27.1	9.0	600	A	A	Black	103.98	
9.4	28.0	9.0	600	A	A	Black	106.98	
8.1	24.3	9.0	600	A	A	Black	91.98	
8.4	24.6	9.0	500	A	A	Black	112.98	HYUNDAI
8.4	25.1	9.0	600	A	A	Black	104.98	
8.4	25.9	9.0	500	A	A	Black	115.98	VOLKSWAGEN
8.4	25.9	9.0	500	A	A	Black	115.98	HYUNDAI
8.9	25.5	9.0	600	A	A	Black	105.98	
8.9	26.3	9.0	500	A	A	Black	112.98	HYUNDAI, KIA
8.9	26.3	9.0	500	A	A	Black	112.98	HYUNDAI, KIA
8.7	27.2	9.0	600	A	A	Black	110.98	
8.9	25.0	9.0	500	A	A	Black	92.98	HYUNDAI
9.2	25.9	9.0	600	A	A	Black	109.98	
9.2	26.8	9.0	600	A	A	Black	113.98	
9.0	27.6	9.0	600	A	A	Black	119.98	
9.3	25.4	9.0	600	A	A	Black	116.98	
9.6	26.3	9.0	600	A	A	Black	116.98	
9.6	27.2	9.0	600	A	A	Black	123.98	
9.6	25.7	9.0	600	A	A	Black	118.98	
10.0	26.7	9.0	600	A	A	Black	125.98	
8.4	25.6	9.0	440	A	A	Black	114.98	
8.9	27.3	9.0	600	A	A	Black	119.98	

9.1	25.1	9.0	500	A	A	Black	115.98	HYUNDAI
8.9	25.9	9.0	600	A	A	Black	117.98	
9.2	26.9	9.0	600	A	A	Black	127.98	
9.2	27.8	9.0	600	A	A	Black	130.98	
9.0	28.6	9.0	600	A	A	Black	122.98	
9.5	25.4	9.0	600	A	A	Black	122.98	
9.3	26.3	9.0	600	A	A	Black	146.98	
9.6	27.3	9.0	600	A	A	Black	144.98	
9.6	28.1	9.0	600	A	A	Black	144.98	
9.8	25.7	9.0	600	A	A	Black	129.98	
9.6	26.7	9.0	600	A	A	Black	135.98	
10.0	27.7	9.0	600	A	A	Black	151.98	
10.0	28.6	9.0	600	A	A	Black	151.98	
9.2	28.8	9.0	600	A	A	Black	174.98	