

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Air (psi)	Max Load (lbs)		Rim		Section Width (inch)	Overall Diameter (inch)	Tread Depth (/32")	U.T.Q.G			Sidewall
								S	D	Measuring	Approved				Treadwear	Traction	Temp.	
10224		205/50R15	XL	89	W	4	50	1,279	-	6.5	5.5-7.5	8.2	23.1	7.5	200	A	A	Black
10251		225/45R15	SL	87	W	4	51	1,201	-	7.5	7.0-8.5	8.9	23.0	7.5	200	A	A	Black
* 10223		245/40R15	SL	88	W	4	51	1,235	-	8.5	8.0-9.5	9.8	22.7	7.5	200	A	A	Black
10211		225/45R17	XL	94	W	4	50	1,477	-	7.5	7.0-8.5	8.9	25.0	7.5	200	A	A	Black
10227		245/40R17	XL	95	W	4	50	1,521	-	8.5	8.0-9.5	9.8	24.7	7.5	200	A	A	Black
10210		255/40R17	XL	98	W	4	50	1,653	-	9.0	8.5-10.0	10.2	25.0	7.5	200	A	A	Black
18120		245/40R18	SL	93	W	4	51	1,433	-	8.5	8.0-9.5	9.8	25.7	7.5	200	A	A	Black
* 10244		255/35R18	XL	94	W	4	50	1,477	-	9.0	8.5-10.0	10.2	25.0	7.5	200	A	A	Black
* 10213		265/35R18	XL	97	W	4	50	1,609	-	9.5	9.0-10.5	10.7	25.3	7.5	200	A	A	Black
* 10203		275/35R18	SL	95	W	4	51	1,521	-	9.5	9.0-11.0	10.9	25.6	7.5	200	A	A	Black
10212		295/40R18	SL	103	W	4	51	1,929	-	10.5	10.0-11.5	11.9	27.3	7.5	200	A	A	Black
* 10199		315/30R18	SL	98	W	4	51	1,653	-	11.0	10.5-11.5	12.6	25.5	7.5	200	A	A	Black
10225		305/30R19	XL	102	W	4	50	1,874	-	11.0	10.5-11.5	12.3	26.3	7.5	200	A	A	Black

. Technical Data can be changed without further notice.

* Available at 2022.2Q