

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Air (psi)	Max Load (lbs)		Rim	
								S	D	Measuring	Approved
14392		235/75R15	RF	109	S	4	50	2,271	-	6.5	6.0~8.0
12764		235/70R16		106	S	4	51	2,094	-	7.0	6.0~8.0
14393		245/70R16	RF	111	S	4	50	2,403	-	7.0	6.5~8.0
12771		245/75R16		111	S	4	51	2,403	-	7.0	6.5~8.0
12760		255/70R16		111	S	4	51	2,403	-	7.5	6.5~8.5
12758		265/70R16		112	S	4	51	2,469	-	8.0	7.0~9.0
12759		265/75R16		116	S	4	51	2,756	-	7.5	7.0~9.0
15211		235/75R17		108	S	4	51	2,205	-	6.5	6.0~8.0
14436		245/65R17	RF	111	S	4	50	2,403	-	7.0	7.0~8.5
12784		245/70R17		110	S	4	51	2,337	-	7.0	6.5~8.0
16049	P	255/70R17		110	S	4	51	2,337	-	7.5	6.5~8.5
16060	P	255/75R17		113	S	4	51	2,535	-	7.0	6.5~8.5
12785		265/65R17		112	T	4	51	2,469	-	8.0	7.5~9.5
13637		265/70R17		115	S	4	51	2,679	-	8.0	7.0~9.0
16061	P	285/70R17		117	T	4	51	2,833	-	8.5	7.5~9.5
15209		255/70R18		113	T	4	51	2,535	-	7.5	6.5~8.5
13123		265/60R18		110	T	4	51	2,337	-	8.0	7.5~9.5
12780		265/65R18		114	S	4	51	2,601	-	8.0	7.5~9.5
15210		265/70R18		116	S	4	51	2,756	-	8.0	7.0~9.0
12774		275/65R18		116	T	4	51	2,756	-	8.0	7.5~9.5
12783		275/55R20	XL	117	T	4	50	2,833	-	8.5	7.5~9.5
13121		275/60R20		115	S	4	51	2,679	-	8.0	7.5~9.5
16055		285/45R22	XL	114	H	4	50	2,601	-	9.5	9.0~10.5
16059		305/45R22	XL	118	T	4	50	2,910	-	10.0	9.5~11.5
12744	LT	235/75R15		104/101	R	6	50	1,985	1,820	6.5	6.0~7.0
13965	LT	215/85R16		115/112	R	10	80	2,680	2,470	6.0	5.5~7.0
12743	LT	225/75R16		115/112	R	10	80	2,680	2,470	6.0	6.0~7.0
12748	LT	235/85R16		120/116	R	10	80	3,042	2,778	6.5	6.0~7.5
12740	LT	245/75R16		120/116	R	10	80	3,042	2,778	7.0	6.5~7.5
12738	LT	265/75R16		123/120	R	10	80	3,415	3,085	7.5	7.0~8.0
16278	LT	285/75R16		126/123	R	10	80	3,750	3,415	8.0	7.5~9.0
16286	LT	315/75R16		127/124	R	10	65	3,860	1,600	8.5	8.0~11.0
13354	LT	235/80R17		120/117	R	10	80	3,085	2,835	6.5	6.0~7.5
13113	LT	245/70R17		119/116	S	10	80	3,000	2,755	7.0	6.5~8.0
12746	LT	245/75R17		121/118	S	10	80	3,195	2,910	7.0	6.5~7.5
12735	LT	265/70R17		121/118	S	10	80	3,195	2,910	8.0	7.0~8.5
15218	LT	285/70R17		121/118	S	10	80	3,195	2,910	8.5	7.5~9.0
16285	LT	285/75R17		121/118	S	10	80	3,195	2,910	8.0	7.5~9.5
16283	LT	315/70R17		121/118	S	10	65	3,195	2,910	9.5	8.0~11.0
15217	LT	265/70R18		124/121	S	10	80	3,527	3,197	8.0	7.0~8.5
15215	LT	275/65R18		123/120	S	10	80	3,415	3,085	8.0	7.5~9.0
14760	LT	275/70R18		125/122	R	10	80	3,640	3,305	8.0	7.0~8.5
15216	LT	285/65R18		125/122	S	10	80	3,640	3,305	8.5	8.0~10.0
16280	LT	295/70R18		129/126	S	10	80	4,080	3,750	8.5	7.5~10.0
15214	LT	265/60R20		121/118	S	10	80	3,195	2,910	8.0	7.5~9.5
16063	LT	275/55R20		120/117	S	10	80	3,085	2,835	8.5	7.5~9.5
16062	LT	275/60R20		123/120	S	10	80	3,415	3,085	8.0	7.5~9.5

13111	LT	275/65R20	126/123	S	10	80	3,750	3,415	8.0	7.5~9.5
15212	LT	285/55R20	122/119	S	10	80	3,305	3,000	9.0	8.0~10.0
17557	LT	285/60R20	125/122	R	10	80	3,640	3,305	8.5	8.0-10.0
16279	LT	295/60R20	126/123	S	10	80	3,750	3,415	8.5	8.0~10.0
15213	LT	305/55R20	121/118	S	10	65	3,195	2,910	9.5	8.5~11.0
12753		30X9.50R15	104	S	6	50	1,985	-	7.5	6.5~8.5
12750		31X10.50R15	109	S	6	50	2,270	-	8.5	7.0~9.0
16282		33X12.50R15	108	R	6	35	2,205	-	10.0	8.5~11.0
16373		35X12.50R18	128	S	12	80	3,970	-	10.0	8.5~11.0
16374		35X12.50R20	125	S	12	80	3,640	-	10.0	8.5~11.0

. Technical Data can be changed without further notice.

. For more detail OE application information, please refer to "Original Equipment 2020" page.

\* Available at 3Q, 2020

+ Different Sidewall

Section	Overall Width (inch)	Tread Diameter (inch)	Tread Depth (/32")	U.T.Q.G			MSRP	F.E.T	OE
				Treadwear	Traction	Temp.			
9.3	28.9	13.0	560	A	B	White	114.98		
9.4	29.0	13.0	560	A	B	White	120.98		
9.8	29.5	13.0	560	A	B	Black	125.98		
9.8	30.5	13.0	560	A	B	White	122.98		
10.2	30.1	13.0	560	A	B	White	130.98		
10.7	30.6	13.0	560	A	B	White	137.98		
10.5	31.7	13.0	560	A	B	White	141.98		
9.3	30.9	13.0	560	A	B	Black	134.98		
9.8	29.5	13.0	560	A	B	Black	136.98		
9.8	30.6	13.0	560	A	B	White	146.98		
10.2	31.1	13.0	560	A	B	White	147.98		
10.0	32.0	13.0	560	A	B	White	150.98		
10.7	30.6	13.0	560	A	B	White	155.98		
10.7	31.7	13.0	560	A	B	White	149.98		
11.5	32.8	13.0	560	A	B	Black	160.98		
10.2	32.1	13.0	560	A	B	White	175.98		
10.7	30.5	13.0	560	A	B	Black	178.98		
10.7	31.5	13.0	560	A	B	Black	185.98		
10.7	32.6	13.0	560	A	B	White	182.98		
11.0	32.1	13.0	560	A	B	Black	185.98		
11.2	31.9	12.0	560	A	B	Black	183.98		
11.0	33.0	12.0	560	A	B	Black	183.98		
11.2	32.1	12.5	560	A	B	Black	230.98		
11.9	32.8	12.5	560	A	B	Black	277.98		
9.3	28.9	16.0	-	-	-	White	128.98		
8.5	30.4	16.0	-	-	-	White	142.98		
8.8	29.3	16.0	-	-	-	Black	140.98		
9.3	31.7	16.0	-	-	-	Black	148.98		
9.8	30.5	16.0	-	-	-	White	157.98		
10.5	31.7	16.0	-	-	-	White	162.98		
11.3	32.8	16.0	-	-	-	White	182.98	2.36	
12.3	34.6	16.0	-	-	-	Black	220.98	3.40	
9.3	31.8	15.0	-	-	-	White	182.98	RAM	
9.8	30.6	16.0	-	-	-	White	164.98		
9.8	31.5	16.0	-	-	-	Black	173.98		
10.7	31.7	16.0	-	-	-	Black	175.98		
11.5	32.8	16.0	-	-	-	Black	191.98		
11.3	33.9	16.0	-	-	-	Black	192.98		
12.7	34.4	16.0	-	-	-	Black	229.98		
10.7	32.6	16.0	-	-	-	White	187.98	0.26	
11.0	32.1	16.0	-	-	-	White	198.98		
11.0	33.2	14.0	-	-	-	Black	195.98	1.32 RAM	
11.5	32.6	16.0	-	-	-	Black	235.98	1.32	
11.8	34.3	16.0	-	-	-	Black	242.98	5.48	
10.7	32.5	16.0	-	-	-	Black	214.98		
11.2	31.9	16.0	-	-	-	Black	210.98		
11.0	33.0	16.0	-	-	-	Black	230.98		

11.0	34.1	16.0	-	-	-	Black	234.98	2.36
11.7	32.4	16.0	-	-	-	Black	271.98	
11.5	33.5	16.0				Black	280.98	1.32
11.8	33.9	16.0	-	-	-	Black	300.98	2.36
12.4	33.2	16.0	-	-	-	Black	297.98	
9.4	29.5	16.0	-	-	-	White	131.98	
10.6	30.5	16.0	-	-	-	White	145.98	
12.5	32.5	16.0	-	-	-	White	135.98	
12.5	34.5	16.0	-	-	-	Black	229.98	4.44
12.5	34.5	16.0	-	-	-	Black	305.98	1.32