

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Air (psi)	Max Load (lbs)		Rim	
								S	D	Measuring	Approved
13137		225/70R15		100	S	4	51	1,764	-	6.5	6.0~7.5
13138		235/70R15		103	S	4	51	1,929	-	7.0	6.0~8.0
13128		235/75R15	XL	109	S	4	50	2,271	-	6.5	6.0~8.0
13132		265/70R15		112	S	4	51	2,469	-	8.0	7.0~9.0
12692		225/70R16		103	T	4	51	1,929	-	6.5	6.0~7.5
13133		225/75R16	XL	108	S	4	50	2,205	-	6.0	6.0~7.5
11725		235/70R16		106	T	4	51	2,094	-	7.0	6.0~8.0
12694		235/75R16		108	T	4	51	2,205	-	6.5	6.0~8.0
14397		245/70R16	RF	111	T	4	50	2,403	-	7.0	6.5~8.0
13130		245/75R16		111	S	4	51	2,403	-	7.0	6.5~8.0
12695		255/65R16		109	H	4	51	2,271	-	7.5	7.0~9.0
11714		255/70R16		111	S	4	51	2,403	-	7.5	6.5~8.5
11716		265/70R16		112	S	4	51	2,469	-	8.0	7.0~9.0
13127		265/75R16		116	T	4	51	2,756	-	7.5	7.0~9.0
13970		275/70R16		114	S	4	51	2,601	-	8.0	7.0~9.0
13131		225/65R17		102	H	4	51	1,874	-	6.5	6.0~8.0
14399		235/65R17	RF	108	H	4	50	2,205	-	7.0	6.5~8.5
13142		235/70R17	XL	111	T	4	50	2,403	-	7.0	6.0~8.0
14396		245/65R17	RF	111	H	4	50	2,403	-	7.0	7.0~8.5
11729		245/70R17		110	T	4	51	2,337	-	7.0	6.5~8.0
13143		255/65R17		110	S	4	51	2,337	-	7.5	7.0~9.0
11740		255/70R17		112	T	4	51	2,469	-	7.5	6.5~8.5
13141		265/65R17		112	H	4	51	2,469	-	8.0	7.5~9.5
11730		265/70R17		115	T	4	51	2,679	-	8.0	7.0~9.0
13136		235/60R18		103	V	4	51	1,929	-	7.0	6.5~8.5
14398		235/65R18	RF	110	H	4	50	2,337	-	7.0	6.5~8.5
13140		245/60R18		105	H	4	51	2,039	-	7.0	7.0~8.5
12696		255/65R18		111	T	4	51	2,403	-	7.5	7.0~9.0
13134		255/70R18		113	T	4	51	2,535	-	7.5	6.5~8.5
13147		265/60R18		110	H	4	51	2,337	-	8.0	7.5~9.5
13139		265/65R18		114	S	4	51	2,601	-	8.0	7.5~9.5
13670		265/70R18		116	S	4	51	2,756	-	8.0	7.0~9.0
11720		275/65R18		116	T	4	51	2,756	-	8.0	7.5~9.5
14327		255/60R19		109	H	4	51	2,271	-	7.5	7.0~9.0
15115		245/60R20		107	H	4	51	2,149	-	7.0	7.0~8.5
15278		275/55R20		113	T	4	51	2,535	-	8.5	7.5~9.5
13144		275/60R20		115	S	4	51	2,679	-	8.0	7.5~9.5
16039		285/45R22	XL	114	H	4	50	2,601	-	9.5	9.0~10.5
11857	LT	215/85R16		115/112	Q	10	80	2,680	2,470	6.0	5.5~7.0
12685	LT	225/75R16		115/112	Q	10	80	2,680	2,470	6.0	6.0~7.0
11859	LT	235/85R16		120/116	Q	10	80	3,042	2,778	6.5	6.0~7.5
11851	LT	245/75R16		120/116	Q	10	80	3,042	2,778	7.0	6.5~7.5
11854	LT	265/75R16		123/120	Q	10	80	3,415	3,085	7.5	7.0~8.0
13353	LT	235/80R17		120/117	R	10	80	3,085	2,835	6.5	6.0~7.5
11855	LT	245/75R17		121/118	S	10	80	3,195	2,910	7.0	6.5~7.5
12812	LT	265/70R17		121/118	R	10	80	3,195	2,910	8.0	7.0~8.5
15116	LT	275/65R18		123/120	S	10	80	3,415	3,085	8.0	7.5~9.0

14007	31X10.50R15	109	S	6	50	2,270	-	8.5	7.0~9.0
-------	-------------	-----	---	---	----	-------	---	-----	---------

. Technical Data can be changed without futher notice.

. For more detail OE application information, please refer to "Original Equipment 2020" page.

Section	Overall Width (inch)	Diameter (inch)	Tread Depth (/32")	U.T.Q.G			Sidewall	MSRP	OE
				Treadwear	Traction	Temp.			
9.0	27.4	12.0	640	A	A	A	White	101.98	
9.4	28.0	12.0	640	A	A	A	White	106.98	
9.3	28.9	12.0	640	A	A	A	White	105.98	
10.7	29.6	12.0	640	A	A	A	White	128.98	
9.0	28.4	12.0	640	A	A	A	White	106.98	
8.8	29.3	12.0	640	A	A	A	White	109.98	
9.4	29.0	12.0	640	A	A	A	White	115.98	
9.3	29.8	12.0	640	A	A	A	White	117.98	
9.8	29.5	12.0	640	A	A	A	White	120.98	
9.8	30.5	12.0	640	A	A	A	White	119.98	
10.2	29.1	12.0	640	A	A	A	White	130.98	
10.2	30.1	12.0	640	A	A	A	White	127.98	
10.7	30.6	12.0	640	A	A	A	White	130.98	
10.5	31.7	12.0	640	A	A	A	White	134.98	
11.0	31.2	12.0	640	A	A	A	Black	156.98	
9.0	28.5	11.0	640	A	A	A	Black	120.98	
9.4	29.1	11.0	640	A	A	A	Black	129.98	
9.4	30.0	12.0	640	A	A	A	White	138.98	
9.8	29.5	11.0	640	A	A	A	White	136.98	
9.8	30.6	12.0	640	A	A	A	White	140.98	
10.2	30.1	12.0	640	A	A	A	White	147.98	
10.2	31.1	12.0	640	A	A	A	White	143.98	
10.7	30.6	12.0	640	A	A	A	Black	149.98	
10.7	31.7	12.0	640	A	A	A	White	142.98	
9.4	29.1	11.0	640	A	A	A	Black	143.98	
9.4	30.0	11.0	640	A	A	A	Black	140.98	
9.8	29.6	11.0	640	A	A	A	Black	150.98	
10.2	31.1	12.0	640	A	A	A	Black	158.98	
10.2	32.1	12.0	640	A	A	A	Black	162.98	
10.7	30.5	12.0	640	A	A	A	Black	157.98	
10.7	31.5	12.0	640	A	A	A	Black	160.98	
10.7	32.6	12.0	640	A	A	A	Black	158.98	
11.0	32.1	12.0	640	A	A	A	Black	170.98	
10.2	31.1	12.0	640	A	A	A	Black	160.98	
9.8	31.5	11.0	640	A	A	A	Black	168.98	
11.2	31.9	10.5	640	A	A	A	Black	170.98	RAM
11.0	33.0	12.0	640	A	A	A	Black	175.98	
11.2	32.1	11.0	640	A	A	A	Black	188.98	
8.5	30.4	13.0	-	-	-	-	Black	130.98	
8.8	29.3	13.0	-	-	-	-	Black	135.98	
9.3	31.7	13.0	-	-	-	-	Black	145.98	
9.8	30.5	13.0	-	-	-	-	Black	149.98	
10.5	31.7	13.0	-	-	-	-	White	160.98	
9.3	31.8	15.0	-	-	-	-	Black	163.98	RAM
9.8	31.5	13.0	-	-	-	-	Black	168.98	
10.7	31.7	13.0	-	-	-	-	White	172.98	
11.0	32.0	13.5	-	-	-	-	White	185.98	

10.6	30.5	13.5	-	-	-	Black	140.98
------	------	------	---	---	---	-------	--------
