

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Air (psi)	Max Load (lbs)		Rim	
								S	D	Measuring	Approved
12805	LT	235/75R15		110/107	Q	8	65	2,335	2,150	6.5	6.0~7.0
14047	LT	215/85R16		115/112	Q	10	80	2,680	2,470	6.0	5.5~7.0
12804	LT	225/75R16		115/112	Q	10	80	2,680	2,470	6.0	6.0~7.0
12808	LT	235/85R16		120/116	Q	10	80	3,042	2,778	6.5	6.0~7.5
12806	LT	245/75R16		120/116	Q	10	80	3,042	2,778	7.0	6.5~7.5
12807	LT	265/75R16		123/120	Q	10	80	3,415	3,085	7.5	7.0~8.0
14044	LT	225/75R17		116/113	Q	10	80	2,755	2,535	6.0	6.0~7.0
14046	LT	235/80R17		120/117	Q	10	80	3,085	2,835	6.5	6.0~7.5
12802	LT	245/70R17		119/116	Q	10	80	3,000	2,755	7.0	6.5~8.0
14045	LT	245/75R17		121/118	Q	10	80	3,195	2,910	7.0	6.5~7.5
14039	LT	265/65R17		120/117	Q	10	80	3,087	2,833	8.0	7.5~9.5
12803	LT	265/70R17		121/118	Q	10	80	3,195	2,910	8.0	7.0~8.5
14048		31X10.50R15		109	Q	6	50	2,270	-	8.5	7.0~9.0
14040		195/70R15C		104/102	R	8	65	1,984	1,874	6.0	5.0~6.0
14041		225/70R15C		112/110	R	8	65	2,469	2,337	6.5	6.0~7.0
14043		195/75R16C		107/105	R	8	69	2,149	2,039	5.5	5.0~6.0
16386		235/65R16C		121/119	R	10	83	3,197	2,998	7.0	6.5~7.5

. Technical Data can be changed without further notice.

. T.S.M.I. #15

. TBA - To Be Announced to selected dealers

Section	Overall	Tread	U.T.Q.G			Sidewall	MSRP
			Width	Diameter	Tread Depth		
9.3	28.9	16.0	-	-	-	Black	TBA
8.5	30.4	16.0	-	-	-	Black	TBA
8.8	29.3	16.0	-	-	-	Black	TBA
9.3	31.7	16.0	-	-	-	Black	TBA
9.8	30.5	16.0	-	-	-	Black	TBA
10.5	31.7	16.0	-	-	-	Black	TBA
8.8	30.3	16.0	-	-	-	Black	TBA
9.3	31.8	16.0	-	-	-	Black	TBA
9.8	30.6	16.0	-	-	-	Black	TBA
9.8	31.5	16.0	-	-	-	Black	TBA
10.7	30.6	16.0	-	-	-	Black	TBA
10.7	31.7	16.0	-	-	-	Black	TBA
10.6	30.5	16.0	-	-	-	Black	TBA
7.9	25.8	12.5	-	-	-	Black	TBA
9.0	27.4	12.5	-	-	-	Black	TBA
7.7	27.5	12.5	-	-	-	Black	TBA
9.4	28.0	12.5	-	-	-	Black	TBA