

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Air (psi)	Max Load (lbs)		Rim		Section Width (inch)	Overall Diameter (inch)	Tread Depth (/32")	U.T.Q.G			Sidewall	MSRP
								S	D	Measuring	Approved				Treadwear	Traction	Temp.		
14435	P	235/55R18	XL	102	V	4	50	1,874	-	7.5	6.5~8.5	9.6	28.1	10.0	500	A	A	Black	127.80
12612		235/60R18	XL	107	V	4	50	2,149	-	7.0	6.5~8.5	9.4	29.1	10.0	500	A	A	Black	130.72
14011		235/65R18	XL	110	V	4	50	2,337	-	7.0	6.5~8.5	9.4	30.0	10.0	500	A	A	Black	127.84
12613	P	245/60R18		104	V	4	51	1,984	-	7.0	7.0~8.5	9.8	29.6	10.0	500	A	A	Black	133.54
12605		255/55R18	XL	109	V	4	50	2,271	-	8.0	7.0~9.0	10.4	29.0	10.0	500	A	A	Black	137.80
14391		255/60R18	RF	112	V	4	50	2,469	-	7.5	7.0~9.0	10.2	30.0	10.0	500	A	A	Black	141.71
12615	P	265/60R18		109	V	4	51	2,271	-	8.0	7.5~9.5	10.7	30.5	10.0	500	A	A	Black	144.60
14058		235/50R19	XL	103	V	4	50	1,929	-	7.5	6.5~8.5	9.6	28.3	10.0	500	A	A	Black	157.69
13122		235/55ZR19	XL	105	W	4	50	2,039	-	7.5	6.5~8.5	9.6	29.2	10.0	500	A	A	Black	154.19
14059		245/55R19		103	V	4	51	1,929	-	7.5	7.0~8.5	10.0	29.6	10.0	500	A	A	Black	154.69
14434		255/50ZR19	RF	107	W	4	50	2,149	-	8.0	7.0~9.0	10.4	29.1	10.0	500	A	A	Black	157.04
14016		235/55R20	XL	105	V	4	50	2,039	-	7.5	6.5~8.5	9.6	30.2	10.0	500	A	A	Black	131.14
14070		245/50R20		102	V	4	51	1,874	-	7.5	7.0~8.5	10.0	29.7	10.0	500	A	A	Black	134.58
12606		255/45R20	XL	105	V	4	50	2,039	-	8.5	8.0~9.5	10.0	29.1	10.0	500	A	A	Black	136.62
14012		255/50ZR20	XL	109	W	4	50	2,771	-	8.0	7.0~9.0	10.4	30.1	10.0	500	A	A	Black	148.42
15092		255/55R20		107	V	4	51	2,149	-	8.0	7.0~9.0	10.4	31.0	10.0	500	A	A	Black	136.54
12607		265/45R20	XL	108	V	4	50	2,205	-	9.0	8.5~10.0	10.5	29.4	10.0	500	A	A	Black	139.41
14021		265/50R20	XL	111	V	4	50	2,403	-	8.5	7.5~9.5	10.9	30.5	10.0	500	A	A	Black	149.84
12617		275/40R20	XL	106	W	4	50	2,094	-	9.5	9.0~10.5	10.9	28.7	10.0	500	A	A	Black	135.33
12608		275/45R20	XL	110	V	4	50	2,337	-	9.0	8.5~10.5	10.7	29.8	10.0	500	A	A	Black	134.43

. Technical Data can be changed without futher notice.