

Product Code	P/LT	Size	XL	L.I	S.S	Ply	Max Load (lbs)			Rim		Section Width (inch)	Overall Diameter (inch)	Tread Depth (/32")	U.T.Q.G			Sidewall	MSRP	F.E.T
							Max Air (psi)	S	D	Measuring	Approved				Treadwear	Traction	Temp.			
15873	LT	265/75R16		123/120	Q	10	80	3,415	3,085	7.5	7.0~8.0	10.5	31.9	19.0	-	-	-	Black	213.27	
15879	LT	285/75R16		126/123	Q	10	80	3,750	3,415	8.0	7.5~9.0	11.3	33.1	19.0	-	-	-	Black	225.66	2.36
15883	LT	235/80R17		120/117	Q	10	80	3,085	2,835	6.5	6.0~7.5	9.3	32.0	18.0	-	-	-	Black	205.35	
15884	LT	245/75R17		121/118	Q	10	80	3,195	2,910	7.0	6.5~7.5	9.8	31.7	18.0	-	-	-	Black	215.79	
15886	LT	255/75R17		111/108	Q	6	50	2,405	2,205	7.0	6.5~8.5	10.0	32.3	18.0	-	-	-	Black	239.77	
15887	LT	265/70R17		121/118	Q	10	80	3,195	2,910	8.0	7.0~8.5	10.7	31.9	19.0	-	-	-	Black	237.63	
15713	LT	285/70R17		121/118	Q	10	80	3,195	2,910	8.5	7.5~9.0	11.0	33.0	19.0	-	-	-	Black	289.46	
15888	LT	295/70R17		121/118	Q	10	80	3,195	2,910	8.5	7.5~10.0	11.8	33.5	20.0	-	-	-	Black	258.66	
15890	LT	305/65R17		121/118	Q	12	80	3,195	2,910	9.0	8.5~11.0	12.2	32.8	20.0	-	-	-	Black	252.64	
15889	LT	315/70R17		121/118	Q	12	80	3,195	2,910	9.5	8.0~11.0	12.7	34.6	20.0	-	-	-	Black	274.61	
15925	LT	275/65R18		123/120	Q	10	80	3,415	3,085	8.0	7.5~9.0	11.0	32.3	19.0	-	-	-	Black	236.95	
15897	LT	275/70R18		125/122	Q	10	80	3,640	3,305	8.0	7.0~8.5	11.0	33.4	19.0	-	-	-	Black	256.06	1.32
15926	LT	285/65R18		125/122	Q	10	80	3,640	3,305	8.5	8.0~10.0	11.5	32.8	19.0	-	-	-	Black	304.22	1.32
15898	LT	295/70R18		129/126	Q	10	80	4,080	3,750	8.5	7.5~10.0	11.8	34.5	20.0	-	-	-	Black	264.54	5.48
15899	LT	305/70R18		126/123	Q	12	80	3,970	3,640	9.0	8.5~10.0	12.2	35.1	20.0	-	-	-	Black	283.06	4.44
15929	LT	275/65R20		126/123	Q	10	80	3,750	3,415	8.0	7.5~9.5	11.0	34.3	19.0	-	-	-	Black	293.46	2.36
15932	LT	285/55R20		122/119	Q	10	80	3,305	3,000	9.0	8.0~10.0	11.7	32.6	19.0	-	-	-	Black	311.07	
15933	LT	295/55R20		123/120	Q	10	80	3,415	3,085	9.5	8.0~10.0	12.2	33.0	20.0	-	-	-	Black	291.41	
15931	LT	295/60R20		126/123	Q	10	80	3,750	3,415	8.5	8.0~10.0	11.8	34.2	20.0	-	-	-	Black	320.55	2.36
15930	LT	295/65R20		129/126	Q	10	80	4,080	3,750	8.5	8.0~10.0	11.8	35.4	20.0	-	-	-	Black	334.93	5.48
16271	LT	305/55R20		125/122	Q	12	80	3,640	3,305	9.5	8.5~11.0	12.4	33.5	20.0	-	-	-	Black	323.72	1.32
15867		33X12.50R15		108	Q	6	35	2,205	-	10.0	8.5~11.0	12.5	32.8	21.0	-	-	-	Black	212.33	
15871		35X12.50R15		113	Q	6	35	2,535	-	10.0	8.5~11.0	12.5	34.8	21.0	-	-	-	Black	218.70	
16261		33X12.50R17		121	Q	12	80	3,195	-	10.0	8.5~11.0	12.5	32.8	21.0	-	-	-	Black	258.16	
16262		35X12.50R17		121	Q	12	80	3,195	-	10.0	8.5~11.0	12.5	34.8	21.0	-	-	-	Black	273.57	
15896		37X12.50R17		121	Q	12	80	3,195	-	10.0	8.5~11.0	12.5	36.8	21.0	-	-	-	Black	289.75	
16263		33X12.50R18		122	Q	12	80	3,305	-	10.0	8.5~11.0	12.5	32.8	21.0	-	-	-	Black	262.57	
16264		35X12.50R18		128	Q	12	80	3,970	-	10.0	8.5~11.0	12.5	34.8	21.0	-	-	-	Black	291.06	4.44
16265		33X12.50R20		119	Q	12	80	3,000	-	10.0	8.5~11.0	12.5	32.8	21.0	-	-	-	Black	295.38	
16266		35X12.50R20		125	Q	12	80	3,640	-	10.0	8.5~11.0	12.5	34.8	21.0	-	-	-	Black	325.83	1.32
16267		37X12.50R20		128	Q	12	80	3,970	-	10.0	8.5~11.0	12.5	36.8	21.0	-	-	-	Black	338.78	4.44
15938		37X13.50R20		127	Q	12	80	3,970	-	11.0	8.5~11.0	13.6	36.8	21.0	-	-	-	Black	377.60	4.44
16270		37X13.50R22		128	Q	12	80	3,970	-	11.0	8.5~11.0	13.6	36.8	21.0	-	-	-	Black	401.70	4.44
16269		35X12.50R22		121	Q	12	80	3,195	-	10.0	8.5~11.0	12.5	34.8	21.0	-	-	-	Black	388.94	
16268		33X12.50R22		114	Q	12	80	2,600	-	10.0	8.5~11.0	12.5	32.8	19.0	-	-	-	Black	334.93	

. Technical Data can be changed without further notice.